PXW 15P

PRODUCT DESCRIPTION:



Specifications:

- Component: 15" Woofer (4 Ohm)

- Environmental conditions: Operational temperature: 5 to 35˚C (41 to 95˚F)

- Operational humidity: 25 to 85% RH (non-condensation) Storage temperature: -20 to 60˚C (4 to 140˚F)

- Frequency Response: (-3dB) : 45Hz ~ 120Hz

- Frequency Range: (-10dB) : 35Hz ~ 120Hz

- Maximum SPL @ 1m: 126dB

- Peak Output @ 1m: 129dB

- Crossover Frequency: 120Hz (12dB/octave)

- Input Type: Balanced Differential

- Input Impedence: 50k

- Input Protection: Level Protected

- Thermal Protection: Input Stage Muting, Auto-Reset

- Low-Frequency Tranducer Diameter: 15" (380mm)

- Voice Coil Diameter: 4" (100mm)

- Low-Frequency Power Amplifier: Rated Power* 500 Watts Continuous, 700 Watts Peak

- Rated THD: < 0.03%

- Cooling: Passive-Heatsink with Speed Sensitive Electric Fan

- Dimensions: 603mm x 436mm x 597mm

- Weight: 59kg

PICTURES:



ADDITIONAL PRODUCTS:



Wheel Board - 185038

AVAILABLE MEDIA ONLINE:

manual english

---

for more information please visit the website:

www.americandj.eu